

INNOVATION AT WORK

weko



WEKO-C3

Special product for improving the absor-
bency of your web material WEKO-C3
accelerates the water absorbcency.

It is required when remoistening is
necessary after a drying process on high-
speed presses. In this case, the wetting
agent WEKO-C3 allows an extremely
fast absorption of the damping fluid,
also where full-area printed surfaces are
concerned. The foaming tendency of
WEKO-C3 is minimal.

Application

The WEKO-C3 has to be diluted in the
damping fluid and applied with the
WEKO Fluid Application system.

Add 0.1 % of WEKO C3 to the damping
fluid. (20ml C3 + 20l H₂O)

WEKO-C3 can be kept for at least 12
months if stored in the sealed original
container at a temperature of less than
+25 °C.

We have different container sizes avail-
able 30 kg container in a one-way can;
Pack of 48 ampoules, each 20 ml and 4
liter containers in a disposable bottle.



weko

C3

FOR MAXIMUM DEMANDS

weko

C3

With the WEKO rotor system you have a totally reliable unit that will give a precise & uniform liquid application with complete accuracy. Your process is repeatable giving you a stable quality for everyday production workflow.



YOUR BENEFITS

- Very good wetting properties
- Food-safe
- Toy-safe
- Foaming agent
- Fine-pored and stable foam
- Less influence on hydrophobic
- Less oleophobic effects

Depending on your needs, single or double sided application, you will find a suitable WEKO solution.

We have various fluids, supply units and rotor carriers - the right system for every application.



WEKO-C3 applied with WEKO Fluid Application System optimizes the product quality and improves the efficiency of your production.

It reduces the size of the individual droplets and thus forms a homogeneous surface of the liquid. The wetting agent has a positive effect on the wetting properties of the surface to be treated.

It is harmless on materials and articles to come into contact with food and can also be applied to toy surfaces.

